CARQ



<u>C</u>OSHH <u>A</u>SSESSMENT <u>R</u>EQUEST FORM

Please return completed Form to Corporate Safety Team along with the relevant Safety Data Sheet.

				,
Name / Designation:	Department / Service: Neighbourhood Service			
Material Code:		office use only	Sypol Subscription No:	office use only
Trade Name:	Ecoplugs Max		Renewal Date:	office use only
Supplier/Manufacturer	: MONSANTO Europe S.A./N.V.			
Material Usage	e Information			
What quantity of the m	aterial is used in one working day? 100		(e.g. kg, litres, approx)	A
How long is the worke	r exposed to the material during the working	day?		
< ½ hour		4 - 8 hours 0	ver 8 hours	Sypol
Where is the material u	used? (Please indicate below)			
Outside	Inside - Well Ventilated Inside - Poorly Ventilated Confined Space			
Other (Please specify)				
Work Practice i.e. Diluting, Mixing, Ha	Information and Applying, Brushing, Spraying etc	Existing Control i.e. Fume Cabinet, Local E		
Recommended application rate at a spacing of 6-8cm for Group 1 trees, 5-6 com for Group 2 trees and 3-4cm for group 3 treesAlways read product label before use.		Chem safe, No specific precautions required when handling unopened packs/containers; follow relevant manual handling advice. Wear CE Marked (or equivalent) nitrile rubber gloves (minimum thickness 0,40 mm). Wash when contaminated. Dispose of when contaminated inside, when perforated or when contamination outside cannot be removed. Wash hands always before eating, drinking, smoking or using the toilet. Wear goggles conforming to EN166 (Field of Use 5 or equivalent). Polyester/cotton or cotton overalls should be worn and should be professionally laundered frequently. When using, do not eat, drink or smoke. Remove soiled clothing immediately and clean thoroughly before using again. Wash hands immediately after work, if necessary take a shower.		