

ENVIROCHEM

Analytical Laboratories Ltd

12 The Gardens, Broadcut, Fareham Hampshire. PO16 8SS

Fibre Counting Report

Our Ref: J116716 FC6

Your Ref: -----

Tel: (01329) 287777 Fax: (01329) 287755

CLIENT:

SITE ADDRESS: HMS Daedalus, Broom Way, Lee On Solent, Hampshire, PO13 9YA

SAMPLING PROTOCOL: Background

Homes & Communities Agency

SAMPLED BY:

DATE OF SAMPLING: 07/03/2017

ANALYSED BY (if different): ----

DATE OF ANALYSIS (if different): -----

r	,				of the body in the body.									
Filter	Pump	Head	Location	Time on	Time off	Flow (litres/min)			Volume	Grats	Fibres	Calculation	Reported	
No.						Flow (start)	Flow (finish)	Flow (used)	(V) litres	(n)	(N)	fibres/ml	result fibres/ml	
FC1	IL2	S1	Building 147, 2F: On landing above main entrance to building	0915	0945	16.0	16.0	16.0	480	200	0.5	0.001	<0.01	
FC2	ENV54	S2	Building 147, 2F: In corridor adjacent wash room	1000	1030	16.0	16.0	16.0	480	200	0.5	0.001	<0.01	
FC3	ENV32	100	Building 147, 2F: By the end of the enclosure furthest away from the stairs and landing	1003	1033	16.0	16.0	16.0	480	200	1	0.001	<0.01	
FC4	IL2	S1	Building 147, 2F: On landing above main entrance to building	1142	1212	16.0	16.0	16.0	480	200	1	0.001	<0.01	
FC5	ENV54	S2	Building 147, 2F: In corridor adjacent wash room	1331	1401	16.0	16.0	16.0	480	200	0.5	0.001	<0.01	
FC6	ENV32	100	Building 147, 2F: By the end of the enclosure furthest away from the stairs and landing	1455	1525	16.0	16.0	16.0	480	200	1.5	0.001	<0.01	

- 1. Unless otherwise stated, the detection limit is 0.01 fibres/ml.
- Comments, observations and opinions are outside the scope of UKAS accreditation.
- 5. For clearance sampling, this report must be read in conjunction with the certificate of reoccupation.

- 2. Samples collected by the client are evaluated using information provided by the client.
- 4. Fibres were counted on membrane filter(s) in accordance with the HSE Guidance Note HSG 248.

Equipment Numbers:

Microscope: Nikon 0853 Stage Micrometer: WSM 13 Tally Counter: S/US

Barometer: Thermometer: BTC 26

BTC 26 Flow Meter:

Temperature (°C): 8 Pressure (mb): Correction Factor (F): ----- Diam. of dust deposit (D) (mm): 22.5 Test Slide (5 bands): Yes/No W/B Grat diameter (µm): 100

Blank Filter Head: Graticules: -----Fibres:

Place of Analysis: RE 61 WPU

Mob Lab

Comments Background monitoring carried out during the building of enclosure in the wash room area on the second floor of Building 147. Results satisfactory.

Environment:

SIGNATURE: (on behalf of Envirochem by an authorised signatory)

PRINT NAME: