

This certificate is not valid if the serial number has been defaced or altered

ICN2/0125922

ELECTRICAL INSTALLATION CERTIFICATE

Issued in accordance with British Standard 7671 - Requirements for Electrical Installations by an Approved Contractor or Conforming Body enrolled with NICEIC, Warwick House, Houghton Hall Park, Houghton Regis, Dunstable, LU5 52X

DETAILS OF THE CLIENT

Client / Address

CCJV, Junction 12, M1, Toddington

Postcode: LUS 6HP

DETAILS OF THE INSTALLATION

The installation is:

Address:

M1 E/1 @ M/P 50/0B (G4)

Postrode

New

Extent of the installation

Power installation supplies to CECLB, CCTV, FTMS and Gantries.

An addition

enstallation covered by this certificate:

An alteration

DESIGN

I/We, being the person(s) responsible for the design of the electrical installation (as indicated by my/our signature(s) below), particulars of which are described above, having exercised reasonable skill and care when carrying out the design, hereby CERTIFY that the design work for which I/we have been responsible is, to the best of my/our knowledge and belief, in accordance with BS 7671 amended to

JANUARY 2008

Details of departures from BS 7671, as amended (Regulations 120.3,133.5):

The extent of liability of the signatory/signatories is limited to the work described above as the subject of this certificate. For the DESIGN of the installation:

** (Where there is divided responsibility for the design)

Signature

Date 14/03/2012

Name (CAPITALS)

Designer 1

Signature

Date 14/03/2012

Name (CAPITALS)

Designer 2

CONSTRUCTION

I/We, being the person(s) responsible for the construction of the electrical installation (as indicated by my/our signature below), particulars of which are described above, having exercised reasonable skill and care when carrying out the construction, hereby CERTIFY that the construction work for which I/we have been responsible is, to the best of my/our knowledge and belief, in accordance with BS 7871 amended to JANUARY 2008 (date)

Details of departures from BS 7671, as amended (Regulations 120.3, 133.5):

The extent of liability of the signatory is limited to the work described above as the subject of this certificate. For the CONSTRUCTION of the installation:

Signature

Date 14/03/2012

Name (CAPITALS)

Constructor

INSPECTION AND TESTING

I/We, being the person(s) responsible for the inspection and testing of the electrical installation (as indicated by my/our signatures below), particulars of which are described above, having exercised reasonable skill and care when carrying out the inspection and testing, hereby CERTIFY that the work for which I/we have been responsible is, to the best of my/our knowledge and belief, in accordance with BS 7671 amended to

JANUARY 2008

Details of departures from BS 7671, as amended (Regulations 120.3,133.5):

The extent of liability of the signatory/signatories is limited to the work described above as the subject of this certificate. For the INSPECTION AND TESTING of the installation:

Signature

Date 14/03/2012

Signature

Date 14/03/2012

Name (CAPITALS)

Inspector

Name (CAPITALS)

Qualified Supervisor†

DESIGN, CONSTRUCTION, INSPECTION AND TESTING

 This box to be completed only where the design, construction, inspection and testing have been the responsibility of one person

1, being the person responsible for the design, construction, inspection and testing of the electrical installation (as indicated by my signature below), particulars of which are described above, having exercised reasonable skill and care when carrying out the design, construction, inspection and testing, hereby CERTIFY that the said work for which I have been responsible is to the best of my knowledge and belief, in accordance with 8S 7671, amended to {date}

Details of departures from BS 7671, as amended (Regulations 120.3,133.5):

The extent of liability of the signatory is limited to the work described above as the subject of this certificate. For the DESIGN , the CONSTRUCTION and the INSPECTION AND TESTING of the installation:

Remewed by

Signature

Date 18/05/2012

Signature

Date 18/05/2012

Name (CAPITALS)

Name (CAPITALS)

Qualified Supervisor††


Where the inspection and testing have been carried out by an Approved Contractor, the inspection and testing results are to be reviewed by the registered Qualified Supervisor.

it there the design, the construction, and the inspection and testing have been the responsibility of one person, the inspection and testing results are to be reviewed by the registered Qualified Supervisor.

Page 1 of

5





SUPP	LY CH	ARACTE	RISTIC	S AND EAR	THING	ARRAN	GEMEN	TS Tick boxes	Tick boxes and enter details, as appropriate						
+System	+System Type(s) +Number and Type of Live Conductors							Natur	re of Sup	ply Para	* Characteristics of Primary Supply				
TN-S	N/A		a.c.	V		d.c.	N/A	Nominal Voltage(s):	230	٧	U₀ m V	Overcurrent Protective Device(s)			
TN-C-S	V	1-phase (2 wire)	N/A	1-phase (3 wire)	V	2 pole	N/A	Nominal frequency, (11)	50	Hz	Notes: (1) by enquiry	BS(EN) 1361			
TN-C	N/A	2-phase (3 wire)	N/A			3 pole	N/A	Prospective fault current, I _{ct} (2(3)	1.08	kA	(2) by enquiry or by measurement	Туре			
TT	N/A	3-phase (3 wire)	N/A	3-phase (4 wire)	N/A	other		External earth fault foop impendance, Ze (2)(3)	0.22	Ω	(3) where more than one supply, record the higher or highest	Rated currem 100 A			
IT	N/A	Other						Number of supplies	1		values (4) by measurement	Short-circuit capacity 33 kA			

PARIL	ULANS U	INSTALLATION A	II THE	URIGIN	Tick boxes and enter details, as appropriate									
#Means of	Earthing	Y.		Detail	ls of Installation	Earth Ele	ctrode (w	here applicabl	e)					
Distribu fac	odity:	Type: (eg rod(s),tape etc)		Location										
Install earth elect	ation N/A	Electrode resistance, R _A :		(Ω)	Method of measurement:									
*Main Switch or Circuit-Breaker * (applicable only where an RCD is suitable and is used as a main circuit-breaker)				Maximum Demand (Load)			Amps			Protective mea				
Type: BS(EN)	60947/3	Voltage rating	250	٧				Protective Bonding Conductors						
No of		Rated			Earthing	totoubnos		Main protective bending conductors			Bandlay of extraneous-conduction			e-parts (v)
Poles	2	current,I _n	100	Α	Conductor material	Copper		Conductor material	Copper		Water service	N/A	Gas Service	N/A
Supply conductors material		RCD operating current, IAn*		mA	Conductor csa	16	mm²	Conductor csa	10	mm²	Oil service	N/A	Structural steel	V
Supply conductors csa	25	mm² RCD operating time (atlΔn)*		ms	Continuity/		V	Continuity/		V	Lightning protection	N/A	Other incoming service(s)	N/A

COMMENTS ON EXISTING INSTALLATION

In the case of an alteration or additions see Section 633 NONE

Note: Enter 'NONE' or, where appropriate, the page number(s) of addional page(s) of comments on the existing installation.

NEXT INSPECTION

§ Enter interval in terms of years, months or weeks, as appropriate

I/We the designer(s), RECOMMEND that this installation is further inspected and tested after an interval of not more than

§ SIX YEARS

Page 2 of

5

[†] Where the Approved Contractor responsible for the construction of the electrical installation has also been responsible for the design and the inspection and testing of that installation, the 'Particulars of the Organisation responsible for the Electrical Installation' may be recorded only in the section entitled 'CONSTRUCTION'

Where a number of sources are available to supply the installation, and where the data given for the primary source may differ from other sources, a separate sheet must be provided which identifies the relevant information relating to each additional source.



SCHED	ULE OF ITEMS INSPECTED † See note below		
	VE MEASURES AGAINST ELECTRIC SHOCK		
	id fault protection	Preventio	on of mutual datrimental influence
Extra low		~	Proximity of non-electrical services and other influences
N/A	SELV N/A PELV	~	Segregation of Band I and Band II circuits or Band II insulation used
Double or r	einforced insulation	V	Segregation of safety Circuits
~	Double or Reinforced Insulation	Identifica	
Racie P	rotection	~	Presence of diagrams, instructions, circuit charts and similar information
		~	Presence of danger notices and other warning notices
~	Insulation of live parts 🧳 Barriers or enclosures	V	Labelling of protective devices, switches and terminals
~	Obstacles ** Placing out of reach **		identification of conductors
Fault pr	rotection	Cables an	d Conductors
	disconnection of supply	V	Selection of conductors for current carrying capacity and
~	Presence of earthing conductor		voltage drop
V	Presence of circuit pretective conductors	Y	Erection methods
	Presence of main protective bonding conductors	~	Routing of cables in prescribed zones Cables incorporating earthed armour or sheath or run in an
	Presence of earthing arrangements for combined protective and functional purposes	~	earthed wring system, or otherwise protected against nails, screws and the like
v	protective and functional purposes Presence of adequate arrangements for alternative source(s), where applicable	~	Additional protection by 30mA RCD for cables concealed in walls (where required,in premises not under the supervision of skilled or instructed persons)
V	FELV		Connection of conductors
~	Choice and setting of protective and monitoring devices (for fault protection and/or overcurrent protection)	~	Presence of fire barriers, suitable seals and protection against thermal effects
Non-condu	cting location **	0	
N/A	Absence of protective conductors	General 🗸	Presence and correct location of appropriate devices for isolation and switching
	equipotential bonding **		Adequacy of access to switchgear and other equipment
NIA	Presence of earth-free equipotential bonding	•	
Electrical s		~	Particular protective measures for special installations and locations
V	For one item of current using equipment For more than one item of current using equipment**	~	Connection of single-pole devices for protection or switching in line conductors only
	To more than one near or current using equipment	*	Correct connection of accessories and equipment
Addition	al protection	~	Presence of undervoltage protective devices
~	Presence of residual current device(s)	~	Selection of equipment and protective measures appropriate to external influences
~	Presence of supplementry bonding conductors	~	Selection of appropriate functional switching devices
** for use	in controlled supervised/conditions only		
SCHEDU	LE OF ITEMS TESTED † See note below	~	Basic protection by barrier or enclosure provided during erection
~	External earth fault loop impendance, Z_{θ}	~	Insulation of non-conducting floors or walls
~	Installation earth electrode resistance, R_{A}	~	Polarity
V	Continuity of protective conductors	~	Earth fault loop impendance,Z _S
N/A	Continuity of ring final circuit conductors	~	Verification of phase sequence
✓	Insulation resistance between live conductors	~	Operation of resudual current devices
V	Insulation resistance between live conductors and Earth	~	Functional testing of assemblies
•	Protection by separation of circuits	~	Verification of voltage drop
SCHEDUL	E OF ADDITIONAL RECORDS* (See attached schedule)		Dana Nafa)
	ral page(s) must be identified by the Electrical Installation Certificate serial number and page number(s).		Page No(s)
	t be completed. 'A' indicates that an inequation or a test two covered out and that the		

[†] All boxes must be completed. 'v' indicates that an inspection or a test was carried out and that the result was satisfactory. 'W/A' indicates that an inspection or a test was not applicable to the particular installation

• Where the electrical works to which this certificate relates includes the installation of a fire alarm system and/or an emergency lighting system (or a part of such system), this electrical safety certificate should be accompanied by the particular certificate(s) for the system(s).

Page 3 of



SCHEDULE OF CIRCUIT DETAILS FOR THE INSTALLATION

	CIRCUIT DETAIL	LS				
TO BE COMPLETED IN EVERY CASE	TO BE COMPLETED ONLY IF THE DISTRIBUT	ION BOARD IS NOT	CONNECTED DIR	ECTLY TO THE ORIGIN	OF THE INSTALLATIO	JN:
Location of 50/0 B distribution board:	Supply to distribution board is from:	A A A A A A A A A A A A A A A A A A A	one with the seconds of the Community	No of phases:	Nominal voltage:	٧
	Overcurrent protective device for the distribution circuit:		RCD (if	Associated any): BS(EN)		
Distribution 50/0 B El	Type: BS(EN)	Rating:	Α	RCD No of poles:	lΔn	n

		·											
1	Circuit designation				condu	rcuit ctors: csa	lion	Overcurrent p	rotective	devices		RCD	7671
Circuit number and phase		Type of wiring (see code)	Reference method	Number of points served	Live (mm²)	Cpc (mm²)	Max. disconnection important time permitted by BS 7671	BS (EN)	Type No	(V)	Short-circuit capacity	© Operating (♥ current, l∆n	Maximum 2s permitted by BS 7671
1	CECLB @ 50/3 B	02	ם	1	70	70	5	88		63	80	finivi	0.82
2	CECLB @ 50/3 B	02	D	1	50	50	5	88		63	80		0.82
3	CECR @ 50/3 A	02	E	1	50	50	5	88		63	80		0.82
	CECLB												
1	HSM CCTV @ M/P 50/4 B	02	D	1	10	10	5	88		16	80		4.18
	CECR												
1	HSM CCTV @ M/P 50/3 A	02	D	1	10	10	5	88		16	80		4.18
2	HSM CCTV @ M/P 50/4 A	02	D	1	10	10	5	88		16	80		4.18
3	AMI LBS1 G4	01	E	1	2.5	2.5	5	60898	С	6	6		3.83
4	AMI LBS2 G4	01	E	1	2.5	2.5	5	60898	C	6	6		3.83
5	AMI LBS3 G4	01	E	1	2.5	2.5	5	60898	С	6	6		3.83
6	AMI LBS4 G4	01	E	1	2.5	2.5	5	60898	С	6	6		3.83
7	MS4 G4	01	E	1	10	10	5	60898	С	20	6		1.15

\$ See Table 4A2 of Appendix 4 of BS 7671

					CODES	FOR TYPE OF	WIRING	
A	B	C	D	E	F	G	Н	O (Other - please state)
Thermoplastic insulated/ sheathed cables	cables	Thermoplastic cables in non-metalic conduit	Thermoplastic cables in metallic trunking	Thermoplastic cables in non-metallic trunking	Thermoplastic /SV/A cables	Thermosetting (SVA cables	Mineral- insulated cables	

^{*} In such cases, details of the distribution (sub-main) circuit(s), together with the test results for the circuit(s), must also be provided, on continuation schedules.

Page 4 of 5

See next page for Schedule of Test Results



SCHEDULE OF TEST RESULTS FOR THE INSTALLATION

					TEST	ESULTS	
TO BE CON	DIRECTLY TO	IF THE DISTRIBUTION BE O THE ORIGIN OF THE INS Distics at this distribution	STALLATION	NECTED			Test instruments (serial numbers) used:
	Confin	mation of supply pola	rity		Earth fault loop impedance	ERH 339	RCD
See note below	Ω	Operating times of associated	At l∆n	ms	Insulation resistance	ERH 339	Other
I _{ry}	kA	RCD (if any)	At 5l _{Δn}	ms	Continuity	ERH 339	Other

a		(ircuit impeda (Ω)	nces			Insulation	esistance		Polarity	measured earth	RCD	operating imes	Τ
Circuit number and phase	Ri (m	ng linal circuits leasured end to	only end)	(At least	circuits one column ompleted)	Line/Line †	Line/Neutral †	Line/Earth †	Neutral/Earth		fault loop impedance, Zs * See note below	at lΔn	at 5f An	Test button operation
Ü	t ₁ (Line)	r _n (Neutral)	r _e (cpc)	R ₁ + R ₂	R ₂	(MΩ)	(MΩ)	(MΩ)	(MΩ)	(4)	(Ω)	(ms)	(ms)	
1	N/A	N/A	N/A	0.27			> 100	> 100	> 100	-	0.09	husi	31157	(4)
2	N/A	N/A	N/A	0.20			> 100	> 100	> 100	~	0.19			1
3	N/A	N/A	N/A	0.5			> 100	> 100	> 100	~	0.42			
1	N/A	NIA	N/A	0.37			> 100	> 100	> 100	~	0.75			
1	N/A	N/A	N/A	0.15			> 100	> 100	> 100	~	0.41			
2	N/A	N/A	N/A	0.28			> 100	> 100	> 100	v	0.63			
3	N/A	N/A	N/A	0.79			> 100	> 100	> 100	~	0.32			
4	N/A	N/A	N/A	0.84			> 100	> 100	> 100	,	0.42			
5	N/A	N/A	N/A	0.94			> 100	> 100	> 100	,	1.45			
6	N/A	N/A	N/A	0.97			> 100	> 100	> 100	>	1.48			
7	N/A	N/A	N/A	0.42			> 100	> 100	> 100	~	0.90			
														\vdash
\vdash														
														\vdash
										\dashv				
														\vdash
										\dashv				_
										\dashv				_

^{*} Note: Where the installation can be supplied by more than one source, such as primary source (eg public supply) and a secondary source (eg standby generator), the higher or highest values must be recorded.

TESTED BY	
Signature:	Position:
Name: (CAPITALS)	Date of testing: 14/03/2012

Page 5 of

5

This form is based on the model shown in Appendix 6 of BS7671 (as amended).
Published by the NICEIC a part of the Ascertiva Group © Copyright The Electrical Safety Council (Jan 2011)

See previous page for Schedule of Circuit Details